

Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Effective date: 8 Feb 2023 Revision: 13

SCGC PVC

Product Name

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name : PG620 (62GP), PG680 (68GP), PG740 (74GP), PG770 (77GP), PC750 (75HC), PF741,

PF682,PF621, PF683, PR701

Chemical Name: Ethene, Chloro-, Homopolymer

Synonyms: Polyvinyl chloride (PVC)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Industrial raw material for plastics processing

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

TPC Paste Resin Co., Ltd.

16, I-1 Road, Map Ta Phut Industrial

Estate, Map Ta Phut, Muang, Rayong,

21150, Thailand

Tel: +66 3892 5200 ext.1395 or 6183

Further information obtainable from:

Technical Services & Development Department

Thai Polyethylene Co., Ltd

Email: pvc_paste@scg.com

1.4 Emergency telephone number:

+66 3892 5200 ext. 6183

SECTION 2: Hazards identification

HMIS® rating (product as packaged) *HMIS is The Hazardous Materials Identification System

Health: 0 Fire: 1 Reactivity: 0

POTENTIAL HEALTH EFFECTS:

Inhalation

Inhalation of dust and vaporization of toxic vapor such as ammonia and residue vinyl chloride monomer (RVCM) may cause irritating to the respiratory tract and breathless. Prolonged inhalation exceeding threshold limit values (TLV) can lead to damaging effect as a result of mechanical overloading of the respiratory tract. RVCM will be decreased by time. (Refer to Section 8 for Exposure Control Information)

Skin contact

Dust may cause irritation to the skin.

Eyes contact

Dust may cause irritation to the eyes.

Ingestion

Email: pvc_paste@scq.com

Not an ordinary cause of exposure. This material is not hazardous under United States Occupational Safety and Health Administrative (OSHA) criteria and Workplace Hazardous Materials Information System (WHMIS) criteria.

TPC Paste Resin Company Limited.

Page |1

www.scgchemicals.com



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Revision: 13

Effective date: 8 Feb 2023

SCGC PVC

Product Name

SECTION 3: Composition/information on ingredients

Chemical characterization:

Component	CAS number	% by Weight
Ethene, chloro-, homopolymer	9002-86-2	>99.5
(PolyVinyl Chloride)	9002-80-2	<u>~</u> 99.5

SECTION 4: First Aid Measures

Inhalation

Remove a patient to fresh air immediately. If the product causes irritant or unwell breathe, a patient should use a bag-valve-mask or similar device to perform artificial respiration (rescue breathing). Get medical attention immediately.

Skin contact

Immediately flush skin with mild soap and large amounts of water until no chemicals remains, Get medical attention

Eye contact

Wash eyes immediately with large amount of water or optic eye lotion, occasionally lifting eyelids until no chemicals remains. Get medical attention if irritation remains.

Ingestion

No effect expected. If large amounts are ingested, get medical attention immediately.

SECTION 5: Firefighting Measures

Extinguishing Media

Dry chemical, carbon dioxide, water, foam

Fire Fighting

Keep unauthorized personnel away, isolate hazard area and deny entry, firefighting with upwind. Wear self-contained breathing apparatus (SCBA) and Personal Protective Equipment (PPE) for firefighters refers to Firefighter Boots, Firefighter Gloves, Firefighters helmets and Fire Resistant cloth.

Hazardous Combustion Products: Hydrogen chloride, Oxides of carbon

SECTION 6: Accidental Release Measures

Personal precautions

Evacuate unnecessary personnel and eliminate all sources of ignition.



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Effective date: 8 Feb 2023 Revision: 13

Product Name

SCGC PVC

Personal protection equipment

Wear personal protection equipment follow by section 8 (Exposure controls / personal protection)

Environmental precautions: Contain spilled chemicals with dike to prevent entry into sewers or waterways. **Method and equipment for cleaning up**

Cleaning spilled Polyvinyl chloride with vacuum to minimize dust emission. Collect spilled materials in appropriate container and identify for disposal.

SECTION 7: Handling and Storage

Handling Procedure:

- Use only in adequate ventilation area and to minimize generation of dust emissions. Preventing accumulation of dust and eliminating potential ignition sources.
- Avoid breathing, contact to skin and eyes by wear personal protection equipment. Wash thorough after handling.
- At temperature higher than 100 deg. Celsius may cause thermal degradation of PVC and forming hydrogen chloride and oxides of carbon. Therefore, using materials at temperature higher than 100 deg. Celsius should also use heat stabilizer.
- Recommend to use the product within 1 year, start from manufacturing date on package, to prevent the coagulation and any changing.
- Additional information can be requested in case of use beyond recommended application, recycle material, or lack of knowledge on proper disposal.
- Recommend to use the operating temperature in controlled range to prevent the resin burn or vaporization of hydrochloric acid, carbon dioxide or other toxic substances. The operating temperature and controlled range depend on actual processing condition; machine type, raw materials, formulation, mold design, production speed, etc. Recommended to use as appropriate, regarding the factors above or contact SCG staff to request the additional information.

Sensitivity to static electricity:

· Electrostatic charges may occur. Grounding system is recommended for processing equipment.

Storage Condition:

- Store in a cool, dry area. Keep away from heat, sparks, flames and other ignition sources. Store in adequate ventilation area. For product arrangement and storage, please study PVC Paste Resin User Manual.
- Regularly clean the working area to prevent the accumulation of dust which can cause the fire and explosion.

www.scgchemicals.com



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Revision: 13

Effective date: 8 Feb 2023

Product Name

SCGC PVC

SECTION 8: Exposure Controls/Personal Protection

Occupational Exposure Limits:

Component	CAS number	United States OSHA Final PEL 8 hour TWA	China OELs	ACGIH:TLV (8 hour TWA)
Ethene, chloro ,homopolymer (PolyVinyl Chloride)	9002- 86-2	15 mg/m3 (total dust) 5 mg/m3 (respirable dust)	5 mg/m3 (TWA) 10 mg/m3 (STEL)	10 mg/m3 (nuisance Dust) 1 mg/m3 (respirable dust)

OEL : Occupational Exposure Level;

TLV : Threshold Limit Values;
TWA : Time Weighted Average;
STEL : Short Term Exposure Level;
PEL : Permissible Exposure Level;

OSHA : United States Occupational Safety and Health Administration; ACGIH : American Conference of Governmental Industrial Hygienists

Engineering controls:

General room ventilation plus local exhaust at points of emission to maintain levels of airborne contaminants below occupational exposure limits

Personal protection equipment:

Respiratory protection:

Wear respirator with high efficiency dust, mist, fume and vapor filters.

Eye protection:

Wear safety glasses or goggles to protect eyes.

Skin and body protection:

Wear suitable protective clothing to minimize skin contact.

Hand Protection:

Wear appropriate chemical resistant gloves.

Other

Emergency shower and eyewash facility should be in workplace close proximity.



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Product Name

SCGC PVC

Effective date: 8 Feb 2023 Revision: 13

SECTION 9: Physical and chemical properties

Physical state : Fine powder, White solid

Change in appearance : Changes color on exposure to heat or light

Odor : Odorless pH : Not applicable

Melting point/freezing point: No data availableBoiling point: Not applicable

Flash point : 736 deg.F or 391deg.C

Evaporation rate : Not applicable

Flammability : Not applicable (Product resists ignition and does not promote flame spread)

Explosive limits: Not applicableVapor pressure: Not applicableVapor density: Not applicable

Specific gravity : 1.4

Water Solubility : Insoluble

Partition Coefficient (octanol/water): No data available **Auto ignition temperature**: 849 deg.F or 454 deg.C

Decomposition temperature: >100 deg.CViscosity: Not applicable

Molecular Formula : $(C_2H_3CI)_n$

Bulk Density : 0.25-0.40 g/cm³

SECTION 10: Stability and Reactivity

Reactivity/Stability:

Stable under standard ambient temperature and pressure (SATP) as a temperature of 298.15 K (25 $^{\circ}$ C, 77 $^{\circ}$ F) and an absolute pressure of exactly 1 atm (101,325 Pa, 1.01325 bar).

Condition to avoid:

Avoid heat, flame, sparks and other sources of ignition.

Incompatibilities/ Materials to Avoid:

Oxidizing materials

Hazardous decomposition products:

Polyvinyl chloride in processing may result the release of very low levels of vinyl chloride, hydrogen chloride and oxides of carbon.

Hazardous Polymerization:

Not hazardous. Polyvinyl chloride is a stable polymer and will not further polymerize and/or re-polymerize to form vinyl chloride monomer.

www.scgchemicals.com



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Effective date: 8 Feb 2023 Revision: 13

Product Name SCGC PVC

SECTION 11: Toxicological Information

Animal Toxicity:

Rats and guinea pigs exposed continuously to PVC dust for 24 hours/day for periods varying from 2 – 7 months were found to have extensive lung damage. In rats, inhalation of fumes from heating process to PVC produced interstitial edema as well as focal bronchial and intra-alveolar hemorrhage. No data is available on the reproductive and mutagenicity effects.

Acute Toxicity:

PVC is practically non-toxic material by ingestion. This material is unlikely to cause skin irritation like other chemicals but physical irritation may occur. Eye irritation may occur from touching of lodged PVC particles. Existing level of Vinyl chloride is not likely to cause an acute biological effect when used in adequate ventilation areas.

Chronic Toxicity:

The available evidence from experimental animals indicates that PVC is not effecting the metabolism in mammals. Existing level of vinyl chloride is not likely to cause a chronic biological effect when used in adequate ventilation areas.

Carcinogenicity:

This product is not classified as a carcinogen by National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) and Occupational Safety and Health Administration (OSHA).

SECTION 12: Ecological Information

Environmental Fate:

Aquatic : No data available

Bioaccumulation : PVC will not biodegrade.

Bioaccumulation : PVC will not bioaccumulation.

Additional Ecological Information: From the fact that PVC is a practically non-toxic to terrestrial organisms.

SECTION 13: Disposal Considerations

Waste Management Information:

Do not dump into any sewers, on the ground, or into any body of water. Any disposal of all waste and contaminate equipment and packaging should be in accordance with all applicable federal and local health and environmental laws and regulations.



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Product Name

SCGC PVC

Effective date: 8 Feb 2023 Revision: 13

SECTION 14: Transport information

SHIPPING NAME:Polyvinyl ChlorideIATA HAZARD CLASS:Not RegulatedDOT HAZARD CLASS:Not RegulatedIMGD CLASS:Not RegulatedDOT SHIPPING ID:Not RequiredRID/ADR CODES:Not RequiredPACKING GROUP:Not RequiredHAZARD ID:Not Required

LABEL: Not Required

SECTION 15: Regulatory information

Label:

This product is not subjected to classification according to Directive 67/548/EEC (Dangerous Substances Directive) by Council of the European Union.

International Regulation Status:

U.S. REGULATIONS: CERCLA SECTIONS 102a / 103 HAZARDOUS SUBSTANCES (40 CFR 302.4): Vinyl chloride: 1 LBS RQ

SARA TITLE II SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40CFR 355.30): Not Regulated SARA TITLE II SARA SECTIONS 311/312 HAZARDOUS CATEGORIES (40CFR 370.21):

Acute : no
Chronic : Yes
Fire : no
Reactive : no
Sudden release : no

SARA TITLE II SECTION 313 (40 CFR 372.65) : Not Regulated OSHA PROCESS SAFETY (29 CFR 1910.119) : Not Regulated

OTHER U.S. REGULATIONS : 29 CFR 1910.1017 (VINYL CHLORIDE)

International Inventory Status:

Canada Chemical Inventory:

Component	DSL	NDSL
Ethene, chloro-,homopolymer	Listed	Not Listed
(PolyVinyl Chloride)		
Vinyl chloride	Listed	Not Listed

^{*}This product is not required as a hazardous material by the U.S. Department of Transportation (DOT), IMGD, EU, United Nations, IATA or the Canadian Transportation of Dangerous Goods (TDG) regulations



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Effective date: 8 Feb 2023 Revision: 13

Product Name SCGC PVC

U.S. Chemical Inventory:

Component	TSCA
Ethene, chloro-,homopolymer	Listed
(PolyVinyl Chloride)	Listeu
Vinyl chloride	Listed

EU Chemical Inventory:

Component	EINECS	NLP	PBT
Ethene, chloro-,homopolymer	Listed	Not Listed	Not Listed
(PolyVinyl Chloride)	Listed	Not Listed	Not Listed
Vinyl chloride	Listed	Not Listed	Not Listed

China Chemical Inventory:

Component	IECSC
Ethene, chloro-,homopolymer	Listed
(PolyVinyl Chloride)	
Vinyl chloride	Listed

Taiwan Chemical Inventory:

Component	NECI
Ethene, chloro-,homopolymer	Listed
(PolyVinyl Chloride)	
Vinyl chloride	Listed

Philippines Chemical Inventory:

Component	PICCS
Ethene, chloro-,homopolymer	Lintad
(PolyVinyl Chloride)	Listed
Vinyl chloride	Listed



Product Name Product Type PVC Paste Resin RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Revision: 13

Australia Chemical Inventory:

Component	AICS
Ethene, chloro-,homopolymer	Listed
(PolyVinyl Chloride)	Listed
Vinyl chloride	Listed

Effective date: 8 Feb 2023

New Zealand Chemical Inventory:

Component	NZIOC
Ethene, chloro-,homopolymer	Listed
(PolyVinyl Chloride)	Listed
Vinyl chloride	Listed

STATE REGULATIONS:

California proposition 65: Known to the state of California to cause the following Vinyl Chloride Cancer (Feb.27, 1987)

SECTION 16: Other information





Abbreviation word:

CAS number : Chemical Abstracts Service Registry Number

IMO : International Maritime OrganizationIMDG : International Maritime Dangerous Goods

ICAO-TI : International Civil Aviation Organization-Technical Instructions for the Safe Transport of Dangerous Goods by Air

IATA-DGR : IATA's Dangerous Goods Regulations

ADR/RID : ADR= Agreement on Dangerous Goods by Road / RID = Regulations concerning The Transport of Dangerous Goods by Rail

AND/ADNR : Inland waterways transport of dangerous goods DSL / NDSL : Domestic/Non-Domestic Substances List

TSCA : Toxic Substances Control Act

EINECS : European Inventory of Existing Commercial Chemical Substances

Page | 9



Product Type

PVC Paste Resin

RY-S-QC-T002 Safety Data Sheet of PVC Paste Resin

Product Name

SCGC PVC

Effective date: 8 Feb 2023 Revision: 13

NLP : No-longer Polymers

PBT : Persistent Bioaccumulative and toxic IECSC : China Existing Chemical Inventory

NECI : National Existing Chemical Inventory in Taiwan

PICCS : Philippine Inventory of Chemicals and Chemical Substances

AICS : Australian Inventory of Chemical Substances

NZIOC : New Zealand Inventory of Chemicals

This Safety Datasheet is valid for all physical forms.

Disclaimer:

- The Applications specified herein is for reference only.
- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of
 merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.

End of Safety Data Sheet

Page | 10