

TECHNICAL DATA SHEET

Product Name
ICORENE®

Product Type

Adhesive LLDPE for Rotational Moulding

Product Grade 1869

Product Description

ICORENE® 1869 is an adhesive linear low density polyethylene powder specifically developed for rotational moulding.

ICORENE® 1869 has been designed using a high performance additive package formulated to provide good bonding to metal surfaces during processing.

Typical Applications

- · Metal coating
- · Lining pipes and tanks

Product Characteristics

- Rotolining
- Corrosion protection
- · Fully UV stabilized
- Natural powder
- · High adhesion
- Excellent bond to pretreated metal
- · Easy processing
- · Good physical properties
- · Corrosion protection

International Compliance

 ICORENE 1869 natural 0000 meets the requirements of U.S. Food and Drug Administration (FDA) 21 CFR Part 177.1520 (c) 3.1a and 177.1520(c) 3.2a

Physical Properties

Property	Test Method	Typical Values	. Unit
Resin Properties			
Melt Flow Rate	ASTM D 1238 @ 190°C, 2.16 kg	3.5	g/10 min
Density	ASTM D 1505 (anneal)	0.927	g/cm ³
Melting Temperature	ASTM D 3418	121 (250)	°C (°F)

Note: the given values are average values for the base resin and should not be used for specification limits.



TECHNICAL DATA SHEET

Product Name

ICORENE®

Product Type

Adhesive LLDPE for Rotational Moulding

Product Grade 1869

Processing Guidelines

Product Technical Assistance

For technical assistance or further information on this product or any other SCG Chemicals' products, please contact your SCG ICO Polymers / SCG Performance Chemicals technical service at the address or telephone number as specified below.

Product Available Forms

Product Packaging

· Natural powder

· 20 kg loose bag

Storage

- · Store in original container in tidy according to the manual of Handling and Storage from Thai Polyethylene Company Limited.
- Product(s) should be stored in dry and dust free location at temperature below 50 °C and protected from direct sunlight
 and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality
 deterioration, which results in odour generation and colour changes and can have negative effects on the physical properties
 of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.



TECHNICAL DATA SHEET

Product Name
ICORENE®

Product Type

Adhesive LLDPE for Rotational Moulding

Product Grade 1869

Safety

- The product is not classified as a hazardous material.
- Please see our Material Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products; for more information, contact your SCG ICO Polymers technical service.

Recycling

- The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.
- Please see our Material Safety Datasheet for details on various aspects of safety, recovery and disposal of the products; for more information, contact your SCG ICO Polymers technical service.

Related Documents

- The latest version of this document will be available at our website, <u>www.scgchemicals.com</u>, or can be obtained from the SCG ICO Polymers technical service.
- The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.
 - Material Safety Datasheet
 - Statement on compliance to food contact regulations

Disclaimer

- The product can be used only for the application as specified here above.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability whatsoever for the accuracy and completeness of such information.
- We make no warranties which extend beyond the description contained herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products
 for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and
 handling of our products.
- No liability can be accepted in respect of the use of our products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.