



# TECHNICAL DATA SHEET

Product Name

**SCG PVC**

Product Type

**Wire & Cable**

Product Grade

**C0805XXX**

## Product Description

C2670XXX is PVC compound product with any color for using in wire and cable application product. The formulation is designed Cable Tape and Non heavy metal which give good process ability by Calendering.

## Typical Application

PVC CABLE TAPE

## Product Characteristics

- Good Process Ability
- Good surface of product
- Non heavy metal

## International

(PVC/APVC/C,PVC/D : ST1)

RoHS

## Physical Properties

Property	Test Method	Typical Value	Unit
Specific Gravity	JIS K 7112	1.29 – 1.32	-
Heat Stability @180°C	JIS K6723	80 – 265	min
Hardness Shore A @10 sec	JIS K6253	72 - 77	-
Volume Resistivity	JIS K6723	0.3 – 1.65 x 10 <sup>13</sup>	Ohm.cm
Tensile Strength	JIS K6723	15 - 16	MPa
Elongation at Break	JIS K6723	291 - 392	%
<b>Aging @ 80°C x 168 hrs.</b>			
Retention of Tensile Strength	JIS K6723	102 - 108	%
Retention of Elongation at Break	JIS K6723	86 - 96	%
Brittleness Temp at -15 °C	JIS K6723	- 25	°C
Bleeding	TPC Method	Not Bleeding	

**Note:** the given values are typical value measured on the product. Values herein are not to be constructed as a product specification.

## Processing Guidelines

The actual processing condition depends on each extruder machine type, screw type and also output needed etc. Generally, temperature at extruder should be around 150-180°C as sequence from feed throat to die head. The exceed temperature than 190°C might effect to appearance, color and typical property.



## TECHNICAL DATA SHEET

Product Name

**SCG PVC**

Product Type

**Wire & Cable**

Product Grade

**C0805XXX**

### Product Technical Assistance

For technical assistance or further information on this product or any other SCG Chemicals' products contact your SCG Chemicals technical service at the address or telephone number as specified below.

### Product Available Form

- Pellet

### Product Packaging

- 25 kg Loose bag
- 25 kg bag Stretch wrap palletized
- 500, 700, 900, and 1,000 kg Flexy bag

### Storage

- Store in original container in tidy according to the manual of Handling and Storage from Thai Polyethylene Company Limited/ Thai Polypropylene Company Limited.
- Product(s) should be stored in dry and dust free location at temperature below 50°C and protected from direct sunlight and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality deterioration, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.

### Safety

- The product is not classified as a hazardous material.
- Please see our Material Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products; for more information, contact your SCG Plastics/SCG Performance Chemicals technical service.

### Recycling

- The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.
- Please see our Material Safety Datasheet for details on various aspects of safety, recovery and disposal of the products; for more information, contact your SCG Plastics/SCG Performance Chemicals technical service.



## TECHNICAL DATA SHEET

Product Name

**SCG PVC**

Product Type

**Wire & Cable**

Product Grade

**C0805XXX**

### Related Documents

- The latest version of this document will be available at our website, [www.scgchemicals.com](http://www.scgchemicals.com), or can be obtained from the SCG Plastics/SCG Performance Chemicals technical service.
- The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.
  - Material Safety Datasheet
  - Statement on compliance to food contact regulations

### Disclaimer

- The Applications specified herein is for reference only.
- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.