

Product Type

Polypropylene

Product Name SCGC™ PP: Homopolymer

Product Grade P304S

Product Description

SCGC[™] PP P304S is a homopolymer polypropylene resin with good process ability and good mechanical properties. It is particularly designed for sheeting and thermoforming products required good stiffness stability, toughness property and clarity.

Typical Application

- Dairy cups
- Disposable drinking cup
- Food containers

Product Characteristics

- Good processability
- Good stiffness
- Good clarity
- Microwavable or hot fillable

International Compliance

- FDA 21 CFR 177.1520
- Regulation (EU) No. 10/2011

Physical Properties

Properties	Test Method	Typical Value	Unit
Melt Flow Rate at 230 °C and 2.16 kg	ASTM D 1238	2.1	g/10 min
Density	ASTM D 1505	0.910	g/cm³
Tensile Strength at Yield	ASTM D 638	330	kg/cm²
Elongation at Yield	ASTM D 638	10	%
Flexural Modulus	ASTM D 790	13,500	kg/cm²
Notched Izod Impact Strength at 23°C	ASTM D 256	58	J/m
HDT at 4.6 kg/cm ²	ASTM D 648	105	°C
Haze (1 mm)	ASTM D 648	61	%

Note: • The given values are typical value measured on the product. Values herein are not to be constructed as a product specification.

• Direct food contact is subjected to the extraction provisions of the regulation on the finished food contact package.



Product Type

Polypropylene

Product Grade P304S

Processing Guidelines

The actual processing condition depends on each machine type, product size and mold design. Generally, Sheet melt temperature should be 200-250°C and cooling temperature range is 20-60°C. Thermoforming heating temperature depends on machine and line speed. Recommend temperature on sheet before forming should be around 148-150°C and cooling temperature range is 15-30°C. The exceed forming temperature than 150°C might affect to product property.

Product Technical Assistance

For technical assistance or further information on this product or any other SCG Chemicals' products, contact your SCG Chemicals technical services at the address as specified below.

Product Available Form

Product Packaging

- 25 kg loose bag
- 25 kg stretch wrap palletized
- 750 kg big bag
- Sea bulk container

Storage

Pellet

- Store in original container in tidy according to the manual of Handling and Storage from Thai Polyethylene Co., Ltd.
- Product(s) should be stored in dry and dust free location at temperature below 50 °C and protected from direct sunlight and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality deterioration, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.

Safety

- The product is not classified as a hazardous material.
- Please see our Material Safety Data Sheet for details on various aspects of safety, recovery, and disposal of the products;

for more information, contact your SCG Chemicals technical services.



Product Name SCGC™ PP: Homopolymer

Polypropylene

Product Grade P304S

Recycling

- The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.
- Please see our Material Safety Datasheet for details on various aspects of safety, recovery and disposal of the products;

for more information, contact your SCG Chemicals technical services.

Product Type

Related Documents

- The latest version of this document will be available at our website, www.scgchemicals.com, or can be obtained from the SCG Chemicals technical services.
- The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.
 - Safety Data Sheet
 - Declaration of Compliance

Disclaimer

- The Applications specified herein is for reference only.
- It is customer's responsibilities to inspect and test the product for suitability of the customer's own use and purpose. The customer is responsible for appropriate, safe, legal use, processing and handling of the product.
- To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication. We however do not assume any liability whatsoever for the accuracy and completeness of the information contained herein.
- We make no warranties which extend beyond the description herein. Nothing herein shall constitute any implied warranty of merchantability or fitness for a particular purpose.
- No liability can be accepted in respect of the use of the product in conjunction with other materials. The information contained herein relates exclusively to the product when it is not used in conjunction with any third party's materials.